



Hot Wheels Ramp Exit Plate Installation

Tools Required:

- #2 Phillips Screwdriver
- 1/4" Hex Driver
- ***Right Angle Pliers *may* be needed for the adjustment of the downward pointing tab after installation (refer to Step 7).

Kit Components:

- (1) Left Ramp Exit Plate - MTL0233-00
- (1) Right Ramp Exit Plate - MTL0233-01
- (4) #8 Flat Washer - WAS0008-00 (2 for each Plate)

Disclaimer Be careful when using hand tools over the playfield. It is recommended to place some foam or a protective covering over the playfield in the area that you are working, in the chance that if a tool is dropped, the covering will help protect from any accidental damage. Installation is performed at your own risk.

Step 1.) Using the #2 Phillips screwdriver, remove the two screws from the Orange Ramp Exit.



Step 2.)

Using the 1/4" Hex Driver, remove the (2) hex spacers.



This is what it will look like with the hex spacers removed:



Step 3.) Gently lift the orange ramp, and place the left Ramp Exit Plate as pictured below, with the tab in the center hole pointed downward.



Step 4.) Using the 1/4" Hex Driver, install the 2 hex spacers that you previously removed.



Step 5.) Carefully align the Ramp so the slots in each side of the ramp line up with the holes in the hex spacers.



Step 6.) Place a washer over the slot in the orange ramp and then fasten the screw back into the hex post, using your #2 Phillips screwdriver. Repeat this step for the other slot in the orange ramp exit. Make sure the fasteners are secure, but do not overtighten.



This is how the Ramp Exit Plate should look when installed from the top-down view.



Almost done with the orange ramp, but not yet! Please be sure to continue to Step 7.

Step 7.) Take a pinball, and place the ball into the ball exit hole to test that the ball will successfully drop down into the inlane. Due to playfield variances, the downward pointing tab may need to be bent back away from the ball entry hole, to allow for space for the ball to successfully fall through into the inlane.

*****Repeat these steps to install the Ramp Exit Plate on the blue ramp.**

